


# Simplicity™ Mirrored Cabinet

Product Specifications: Residential

**ELECTRIC MIRROR®**



## FEATURES AND BENEFITS

- Copper-free, corrosion-resistant OmegaMirror™
- Matte silver aluminum cabinet body
- Wide 140° door swing for optimized usage
- Edge-guard protective trim around entire mirror door
- Soft close, adjustable damping, quiet landing, and fast close hinges
- Easy-mount hinge system for simple installation
- Mirrored interior with automatic top light
- Magnetic strip for small personal grooming tools
- Adjustable glass shelves
- Surface mounting kit included
- Interior 20 Amp, 120V AC duplex receptacle with Type A and C USB charging ports
- 400-hour CASS testing ensures suitability for high-moisture environments
- Environmentally sustainable
- Energy efficient
- Easy installation
- ADA compliant
- 3-year limited warranty
- Covered by one or more patents
- Designed in America and sourced globally

## AVAILABLE OPTIONS

- Ganging Kit for installation of side-by-side mirrored cabinets
- Right or left door swing

## SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards

## PRODUCT DESCRIPTION

Simplicity™, in both form and function, can easily accentuate any design style you choose. It features exceptional reflectivity, glass shelving, and conveniently placed integrated outlets.

## SPECIFICATION STATEMENT

Solution shall consist of a mirrored cabinet with corrosion-resistant glass and a 3-year limited warranty. Mirror shall have met 400-hour salt and corrosion CASS Test Standard.

## THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S.-based customer service support
- ☑ 125,000-square-foot American manufacturing facility



## INSTALLATION SPECIFICATIONS

- 120V hardwire electrical connection; provide a 12" whip; junction box not required; interior outlet requires unswitched 20 Amp GFCI protected circuit; refer to installation instructions for further details and options
- Internal top light controlled by internal PIR sensor
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

## MODELS

Base Model with Left Hinge*	Base Model with Right Hinge*	Fixture Dimensions	Rough-In Dimensions	Power Requirements
SIM-2340-LT	SIM-2340-RT	23.25"W x 40.00"H x 4.65"D (591mm x 1016mm x 118mm)	22.36"W x 38.62"H x 3.93"D (568mm x 981mm x 100mm)	120 VAC, 6W

\*Base model number listed. To specify additional options, contact [residential@electricmirror.com](mailto:residential@electricmirror.com).

## DIMENSIONAL DRAWING (Not to scale)

